

# WATERTAP WATER FAUCET 490



IR sensor  
Wall-mounted  
Stainless Steel with black PVD coating  
2-year warranty


DAN DRYER WaterTap features a minimalist, modern design in stainless steel with black PVD coating. The water faucet is part of a complete product line, which also includes hand dryer and soap dispenser. The product line is available for either deck or wall mounting.

## Technical data

Type	WATERTAP WATER FAUCET Prod. No.: 490 Touch-less water faucet with IR sensor	WATERTAP WATER FAUCET Prod. No.: 490 Touch-less water faucet with IR sensor
Dimension	Ø50/Ø38 x 220 mm	Ø1.96"/Ø1.49" x 8.66"
Material	Stainless steel	Stainless steel
Power connection	AC (6V)	AC (6V)
Wattage standby mode	Less than 0.1 W	Less than 0.1 W
Water pressure	10-100 PS	10-100 PS
Water temperature	4-85° C	39.2-185 F
Activation time	0.5-1 sec	0.5-1 sec
Flow rate	Less than 3.8 l/min.	Less than 3.8 l/min.
Net weight	1.55 kg	3.41 lb
IP rating	IP35	IP35
Tender text	Touch-less water tap in stainless steel with black PVD coating finish for wall top mounting. Infra-red sensor and electronic timer, power connection AC (6V), IP35, water pressure 10-100 PSI, water temperature 4-85°C, activation 0.5-1 sec., flow rate <3.8 l/min. Net weight: 1.55 kg.	Touch-less water tap in stainless steel with black PVD coating for table top mounting. Infra-red sensor and electronic timer, power connection AC (6V), IP35, water pressure 10-100 PSI, water temperature 39.2-185 F, activation 0.5-1 sec., flow rate < 3.8 l/min. Net weight: 3.41 lb

## Application

DAN DRYER WaterTap with automatic sensor for touch-less activation is a hygienic solution for commercial washrooms. It is easy to operate and simple to manage by all kinds of users, including children and people with reduced hand mobility. The DAN DRYER Tap range is an ideal build-in solution for construction projects and automatic hand wash stations.



## References

Shopping centres, restaurants, hotels, airports, sports facilities, schools and public institutions.

## Standard colour

Black PVD coating.

## Activation

Infrared sensor and electronic timer. Touchfree. Activation distance adjustable between 20 - 120 mm / 0.78"- 4.72".

## Installation

Machine intended for wall mounting. Connection to fixed installation or via circuitbreaker. Installation must be carried out by a qualified electrician.

## Approval

