



TSI-PRM BJÖRK BABY CHANGING STATION 3230

Wall mounted
Powder coated aluminium
Compliant to rolling stock norms
2-year warranty



reddot design award
best of the best

DAN DRYER TSI-PRM wall mounted baby changing station with a carrying capacity that exceeds TSI-PRM requirements. Suitable for installation on board rolling stock.

Technical data

	Metric	Imperial
Type	TSI-PRM BJÖRK BABY CHANGING STATION Prod. No.: 3230 Baby changing station	TSI-PRM BJÖRK BABY CHANGING STATION Prod. No.: 3230 Baby changing station
Width	552 mm	21.73"
Depth (folded up)	100 mm	3.93"
Depth (folded down)	751 mm	29.56"
Height (folded up)	771 mm	30.35"
Height (folded down)	322 mm	12.67"
Changing surface	L: 700 mm x B: 510 mm	L 27.55" x W 20.07"
Load capacity	80 kg	176.37 lb
Recommended working height	950 mm above floor	37.40" above floor
Force required to open	~25 N; to close: ~25 N	~25 N; to close: ~25 N
Net weight	17 kg	37.47 lb

Compliant to the following rolling stock norms

- TSI-PRM 1300/2014/EU
- EN 45545-2:2013 + A1:2015
- EN 61373:2010 Category 1 Class B
- EN 71-3:2013+A1:2014

Function

Torsion springs ensure the smooth and easy opening and closing motion of the changing station.

Product is approved according to EN 12221-1:2008 + A1:2013.

Materials

Changing surface: Powder coated aluminium profile. Wall mounting: Powder coated steel plate. Axle and levers: Electro-galvanised steel.

Paint

Tested to comply with EU standard EN 71/3.

Colour

White, RAL 9003.
Structure: Smooth.
Gloss: 75.
Other colours and coatings on request.

